

Wind Power

Accumulator and Cooler Products for Wind Power Applications





ENGINEERING YOUR SUCCESS.

Accumulators and Coolers are used for many applications in the wind turbine. The demands that are placed on the product are distinctly different depending on the location and the application requirements, which heavily influence the product selection process.

One thing is common to both however, and that is the criticality of reliability and product lifetime, as unscheduled maintenance is normally very expensive due to the costs associated with system downtime, the need for skilled technicians, the location of the turbine itself and the fact that the nacelles can be up to 100 meter high!

Extreme Forces

Accumulators

When accumulators of any type are mounted in the hub of the turbine, they are subjected to extreme forces and vibration due to the forces generated as the hub is turning. Also, when used in pitch control, the accumulators are working 100% of the time whilst the hub is turning, adjusting the blades many times per minute. Regardless of the technology used, these factors can lead to premature failure of

Applications

Wind Turbines

- Pitch Systems
- Pitch Gear Box
- Shaft Brake
- Yaw Brake
- Yaw Drive

components, if they have not been adequately designed & tested for these conditions. Furthermore, the accumulators can also be used to supply power for an emergency stop situation where the criticality of being available for use is high.

Continuous Development

We have developed a special rilsan coating on the accumulator shell, which has the purpose of drastically reducing the friction between bladder and shell surface in a very cost effective way. This also has the primary goal of increasing product life, but also has additional benefits of providing excellent corrosion protection, whilst minimising any future contamination of the system hydraulic oil as there is extremely little abrasion between the working components to produce particles in the hydraulic system. Once more, the process of applying this coating

is technically complex and provides a high level of confidence to our customers, as any non adhesion of coating can cause early system failure and damage to some of the more expensive items within the hydraulic system.

Advanced Technology

We work with our customers to develop specific rubber compounds for our bladder, which meet the needs of this application in an optimum way.

Our latest bladder with E2 bladder mix has been specifically designed for the rigours of the hub and has extended product lifetime by 3 times longer.

Coolers

We are a trusted partner for coolers to some of the world's leading producers of hydraulic power packs. We believe that this is due to our "best in class" product range, that has been developed over many years for industrial applications but is highly appropriate for use here.

We have also built up a wealth of experience supplying coolers within the gearbox hydraulic circuit. This is a demanding application due to the high viscosity and flow rates that are required for the cooler to withstand. Whether the purchasing decision is made by the wind turbine manufacturer or the producer of the gearbox, we have the tools at our disposal to be your ideal development partner. Cooling of the generator and electrical cabinet are other fields of application.

Applications

Wind Turbines

- Power Packs
- Gear Box
- Generator and Electrical Cabinet

Closed Loop System

Accumulator maintenance can be a significant issue in applications where the product is working in severe conditions and/or difficult to access. Field maintenance is expensive and generates health & safety concerns.

Parker Olaer has developed an automated nitrogen top-up system for gas charging of accumulators. This ensures accumulators are pre-charged to an accurate level and reduces human intervention on site, providing a virtually maintenance free solution.

Plate Water Oil Coolers (PWO Series)

The unique PWO design features result in a turbulent oil and cooling water flow, the key to high cooling capacity. This turbulent flow prevents clogging, a frequent cause to reduced cooling capacity. PWO provides an oil temperature very close to the inlet cooling water temperature, eliminating the need for an active cooling system in certain applications.

Diaphragm Accumulators (ELM Series)

Diaphragm accumulators are used on hydraulic powerpacks within the nacelle for pitch control and brake applications.

This product series is often utilized in hydraulic systems that are subject to sudden variations of pressure and help to maintain pressure during these fluctuations or failures.

Air Oil Cooler for Marine & Offshore Applications (MAC Series)

The MAC series is engineered for Marine nearshore and offshore applications and provides cooling capacity up to 300 kW. Corrosion resistance meets C4-M and C5M-M requirements in accordance with ISO 12944.

Bladder Accumulators (EHV Series) - with Rilsan Coating and E2 Bladder Mix

Bladder accumulators are the predominant technology being used today when accumulators need to be >10 litres in size, whether in the hub or the nacelle. They are ideal when price, space or weight is at a premium. Visually similar to "standard accumulators", they are very different and specifically designed for use in this application.


Piston Accumulators (EHP Series)

This product is an ideal solution in applications where the compression ratio between gas and oil needs to be high, oil cleanliness is assured and where the customer may want to more easily monitor gas pressure.

Our piston accumulators have been specifically designed and tested for the rigours of this application and are being used by a number of the world's leading wind turbine producers.

Modul'Air

A compact system comprising of high performance accumulators for the hub in offshore wind turbines - 8MW.



· SICHER OF OF OF OF O OR OS. IN PRODUCTION

beaus/Explicit version CD.L. Thu Nov 13 25:

We have invested heavily in our expert team of people who have a unique set of experience, hardware and software to be the leading development partner.

SECTI HA RIS

-

Working closely with our customers, we are able to accurately model the behaviour of the product in the field. Both by computer simulation and by physical product testing, we can ensure the best possible functionality.



Step: Step: 1 Increment 6396: Step Time = 0.1000 Primary Var: S, Mises Deformed Var: U Deformation Scale Factor: +1.000e+00











Regulations

Accumulators

Due to our vast experience in demanding markets such as renewable energy, we are offering an unmatchable range of rubber compounds to meet the most difficult applications. Parker Olaer products are supported all over the globe, and we will meet customer requirements wherever needed.

We therefore offer the complete range of approvals, such as all key Marine

approvals (BV, DNV, ABS, LR, ...), over and above all country specific approvals (PED, ASME, SELO, CRN, ARH, CUTR, ...).

Service Centre Network

Parker Hannifin has developed a network of trained competent persons within Authorized Recertification/ Service Centres.

Services include: -

- Preparation of Written Schemes of Examination
- Accumulator maintenance, testing and repair
- Hydraulic system troubleshooting
- Product in stock

Parker Authorized Recertification Centres are fully trained and offer a wealth of experience in the Parker accumulator and cooler product range.

Parker Worldwide

Europe, Middle East, Africa

AE – United Arab Emirates, Dubai Tel: +971 4 8127100 parker.me@parker.com

AT – Austria, Wiener Neustadt Tel: +43 (0)2622 23501-0 parker.austria@parker.com

AT – Eastern Europe, Wiener Neustadt Tel: +43 (0)2622 23501 900 parker.easteurope@parker.com

AZ - Azerbaijan, Baku Tel: +994 50 22 33 458 parker.azerbaijan@parker.com

BE/LU – Belgium, Nivelles Tel: +32 (0)67 280 900 parker.belgium@parker.com

BG - Bulgaria, Sofia Tel: +359 2 980 1344 parker.bulgaria@parker.com

BY – Belarus, Minsk Tel: +48 (0)22 573 24 00 parker.poland@parker.com

CH – Switzerland, Etoy Tel: +41 (0)21 821 87 00 parker.switzerland@parker.com

CZ – Czech Republic, Klecany Tel: +420 284 083 111 parker.czechrepublic@parker.com

DE – Germany, Kaarst Tel: +49 (0)2131 4016 0 parker.germany@parker.com

DK – Denmark, Ballerup Tel: +45 43 56 04 00 parker.denmark@parker.com

ES – Spain, Madrid Tel: +34 902 330 001 parker.spain@parker.com

FI – Finland, Vantaa Tel: +358 (0)20 753 2500 parker.finland@parker.com

FR – France, Contamine s/Arve Tel: +33 (0)4 50 25 80 25 parker.france@parker.com

GR – Greece, Athens Tel: +30 210 933 6450 parker.greece@parker.com **HU – Hungary,** Budaoers Tel: +36 23 885 470 parker.hungary@parker.com

IE – Ireland, Dublin Tel: +353 (0)1 466 6370 parker.ireland@parker.com

IT – Italy, Corsico (MI) Tel: +39 02 45 19 21 parker.italy@parker.com

KZ – Kazakhstan, Almaty Tel: +7 7273 561 000 parker.easteurope@parker.com

NL – The Netherlands, Oldenzaal Tel: +31 (0)541 585 000 parker.nl@parker.com

NO – Norway, Asker Tel: +47 66 75 34 00 parker.norway@parker.com

PL – Poland, Warsaw Tel: +48 (0)22 573 24 00 parker.poland@parker.com

PT – Portugal, Leca da Palmeira Tel: +351 22 999 7360 parker.portugal@parker.com

RO – Romania, Bucharest Tel: +40 21 252 1382 parker.romania@parker.com

RU – Russia, Moscow Tel: +7 495 645-2156 parker.russia@parker.com

SE – Sweden, Spånga Tel: +46 (0)8 59 79 50 00 parker.sweden@parker.com

SK – Slovakia, Banská Bystrica Tel: +421 484 162 252 parker.slovakia@parker.com

SL – Slovenia, Novo Mesto Tel: +386 7 337 6650 parker.slovenia@parker.com

TR – Turkey, Istanbul Tel: +90 216 4997081 parker.turkey@parker.com

UA – Ukraine, Kiev Tel: +48 (0)22 573 24 00 parker.poland@parker.com

UK – United Kingdom, Warwick Tel: +44 (0)1926 317 878 parker.uk@parker.com

ZA – South Africa, Kempton Park Tel: +27 (0)11 961 0700 parker.southafrica@parker.com

North America

CA – Canada, Milton, Ontario Tel: +1 905 693 3000

US – USA, Cleveland (industrial) Tel: +1 216 896 3000

US – USA, Elk Grove Village (mobile) Tel: +1 847 258 6200

Asia Pacific

AU – Australia, Castle Hill Tel: +61 (0)2-9634 7777

CN – China, Shanghai Tel: +86 21 2899 5000

HK – Hong Kong Tel: +852 2428 8008

ID – Indonesia, Tangerang Tel: +62 21 7588 1906

IN – India, Mumbai Tel: +91 22 6513 7081-85

JP – Japan, Fujisawa Tel: +81 (0)4 6635 3050

KR – South Korea, Seoul Tel: +82 2 559 0400

MY – Malaysia, Shah Alam Tel: +60 3 7849 0800

NZ – New Zealand, Mt Wellington Tel: +64 9 574 1744

SG – Singapore Tel: +65 6887 6300

TH – Thailand, Bangkok Tel: +662 186 7000

TW – Taiwan, New Taipei City Tel: +886 2 2298 8987

VN – Vietnam, Ho Chi Minh City Tel: +84 8 3999 1600

South America

AR – Argentina, Buenos Aires Tel: +54 3327 44 4129

BR – Brazil, Cachoeirinha RS Tel: +55 51 3470 9144

CL – Chile, Santiago Tel: +56 2 623 1216

MX – Mexico, Toluca Tel: +52 72 2275 4200

Ed. 2015-04-21

© 2016 Parker Hannifin Corporation. All rights reserved.



Catalogue HY10-5001/UK, POD, 09/2016, ZZ

EMEA Product Information Centre Free phone: 00 800 27 27 5374 (from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL, IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

US Product Information Centre Toll-free number: 1-800-27 27 537 www.parker.com